## Conversion of Single Family Dwelling to Office (B) Occupancy December 2014

MN licensed architect to prepare and sign construction plans. Items listed below are typical but not necessarily a complete list. Applicant to submit two copies of plans to Minneapolis Development Review for permitting.

- 1. Accessible route from city sidewalk to building entrance.
- 2. 36" entrance door with accessible hardware.
- 3. Accessible route throughout 1<sup>st</sup> floor. Minimum net clear opening dimension of 32" shall be provided at doors or openings to each room. Accessible hardware required at doors.
- 4. Less than 3000 sq. ft. of office space on other floors (total) does not require accessible route to those other floors. More than 3000 sq. ft. and/or occupant load of 30 require an elevator or lift be provided.
- 5. Provide a minimum of one accessible restroom on the accessible level (one unisex/gender neutral restroom ok). If other restrooms are added they are also required to comply, even if not on an accessible level.
- 6. Basements greater than 1500 sq. ft. require fire department openings, or are to be sprinklered. Basements less than 1500 sq. ft. do not.
- 7. Basements to be separated per IBC 413.
- 8. Architect or engineer to verify that floors used for office meet floor loading requirements.
- 9. Additional requirements may apply if the building will be mixed occupancy.

Zoning approval and SAC determination are required prior to the building permit being issued.